

UTILISING ARTIFICIAL NEURAL NETWORK AND REPRO-MODELLING IN TURBULENT COMBUSTION

F.C. Christo, A.R. Masri, and E.M. Nebot

Department of Mechanical and Mechatronic Engineering
The University of Sydney, NSW 2006, Australia

and

T. Turányi*

School of Chemistry, University of Leeds, U.K.

email: christo@rasha.me.su.oz.au

ABSTRACT

Two techniques, Artificial Neural Network (ANN) and Re-pro-Modelling (RM), are successfully used to represent the chemistry in turbulent combustion simulations. This is a novel application of both methods which show satisfactory accuracy in representing the chemical source term, and good ability in capturing the general behaviour of chemical reactions. The ANN model, however exhibits better generalisation features over those of the RM approach. In terms of computational performance, the memory demand for handling the chemistry term is practically negligible for both methods. The total Central Processing Unit (CPU) time for Monte Carlo simulation of turbulent jet diffusion flame, which is dictated mainly by the time required to resolve the chemical reactions, is smaller if the RM method is used to represent the chemistry, in comparison to the time required by the ANN model. The potential and capabilities of these techniques are extendable to handle the chemistry of different fuels, and more complex chemical mechanisms.

1. Introduction

The adequate representation of chemistry in reacting systems is one of the outstanding problems in turbulent combustion. This is mainly due to the complexity and highly non-linear nature of high temperature chemical reactions. A proper kinetic mechanism to describe the chemistry of a simple fuel like hydrogen, for example, may contain several tens of reactions and more than ten species. Although the systematic reduction of chemical kinetic sets to a manageable size of about 3-5 global reactions is possible [1], the numerical simulation of turbulent combustion remains computationally prohibitive. If look-up tables are used to store the changes in composition due to chemical reaction over specified time intervals, then the computer memory (storage) requirements would become extremely large. Alternatively, the computational run time would increase dramatically if the Ordinary Differential Equations (ODEs) representing the production rates of species are directly integrated during the simulation.

The objective of this paper is to outline a novel approach for representing chemical reactions in turbulent combustion simulations with a modest requirement of memory storage and CPU time. The principle is to produce mathematical equations which describe the chemical behaviour of a system given a set of compositions and reaction time scales. Two methods are used to describe such formulation: Artificial Neural Networks (ANN) and Re-pro-Modelling (RM). This is yet another genuine application of ANN which are widely used in many aspects of science and engineering. The intrinsic capability of ANN in approximating non-linear systems [2, 3] is essential for representing chemical reactions which are highly

*Permanent address: Central Research Institute for Chemistry, H-1525 Budapest, P.O.Box 17, Hungary

non-linear functions of temperature and species concentrations. The Repro-Modeling approach establishes functional relations in the form of high-order multivariate polynomials between a set of inputs and outputs. This method has recently been used for combustion simulation by Turányi [4]. Both ANN and RM methods use a training set of inputs and outputs which is generated separately and corresponds to chemical compositions that are accessible during the actual simulation. Since the problem is geared toward accounting for chemical reactions in turbulent combustion simulations, the training set is generated from the chemical system of $H_2/CO_2/O_2$ mixtures using a three-step reduced chemical mechanism [5]. A representative set of values for four scalars (mixture fraction, and molar abundance of CO_2 , H, and H_2O) are used here as input and the output represents the change in composition of the reactive scalars; CO_2 , H, and H_2O ; over a certain reaction time. Although a specific fuel and chemical kinetic scheme is used here, the method can be extended to other fuel mixtures and more complex chemical kinetic mechanisms.

2. Artificial Neural Network Training

The neural network architecture used for this study is a multi-layer perceptron (MLP) that consists of an input layer, an output layer, and two intermediate (*hidden*) layers. A hyperbolic-tangent function is used as a transfer (activation) function. An equal number of neurons in each hidden layer is used as it proved (by trial and error experiments) that it is easier to train MLP network if the number of neurons in the internal layers are balanced. Significant differences in the number of neurons causes a 'bottleneck' junction of information that severely affect the convergence of the algorithm [7]. Similar observations




Figure 1: A typical neural network prediction (in normalised units) showing the training subset, the original samples, and the associated errors.

have been reported by deVilliers and Bernard [6]. The learning algorithm used is the backpropagation scheme with an individual adaptive learning rate factors for the weight matrices and bias vectors. A constant value for the momentum term factor is used. The details of the optimisation process and sensitivity analysis of the architecture and topology of the network are described by Christo et al. [7].

In order to reduce the possibility of being trapped in local minima, the training of the ANN is carried

out using a subset of the original training samples. The training subset is generated randomly during the learning process. To achieve smooth behaviour of the algorithm, the size of the subset should be 70%-80% of the size of the training set (see Fig. 1). This continuous (dynamic) randomisation of the subset of the training samples is found to give superior performance, in terms of convergence rate, over using a fixed set of preselected training samples.

Figure 2 shows the actual and the associated errors of the ANN model in approximating the incremental changes $\Delta\Gamma_{CO_2}$ (kmol/kg) of the reactive scalar, CO_2 over reaction time $\Delta t \approx 1.56\mu s$. The small




Figure 2: Neural network and Re-pro-modelling approximation of composition changes of Carbon dioxide, $\Delta\Gamma_{CO_2}$, over reaction time of $1.56\mu s$, and the associated absolute errors (for clarity, the errors distributions are shifted by a fixed interval).

magnitude of the errors and their uniform distribution implies that satisfactory convergence of the ANN algorithm is achieved over the entire range of the training set, and is not confined only to the subset domain.

3. Re-pro-Modelling Training

Re-pro-modelling (RM) means the approximation of a sophisticated, time consuming computational model by a simple empirical model consisting of one or several explicit functions. In the special case of the RM approach called 'parameterisation' technique, an explicit algebraic formulation is obtained by numerical fitting of functions to the numerical solution of the differential equations which describe the chemical reaction. The input-output samples are fitted by a least-square approximation with high order multivariate orthonormal polynomial using the Gram-Schmidt algorithm [8]. To reduce the computational cost in evaluating the multivariate polynomials due to unnecessary multiplications, an appropriate factorisation, *i.e.* Horner equation, is used. The algorithm used does not ensure an optimal factorisation, but the result is close to optimal.

The accuracy of the RM functions in representing the compositional changes $\Delta\Gamma_{CO_2}$ (kmol/kg) over

reaction time of $\approx 1.56\mu s$ is shown in Fig. 2. The figure clearly shows good approximation indicated by small and uniformly distributed errors across the entire samples space.

4. Discussion

To examine the generalisation capabilities of both methods, the ANN model and RM functions are then used to approximate a set of compositions that are collected from a Monte Carlo (MC) simulation of a turbulent diffusion flame of H_2/CO_2 fuel using the probability density function approach [7, 9]. The absolute errors obtained in approximating $\Delta\Gamma_{CO_2}$ for a reaction time of $12.5\mu s$ using ANN and RM methods are shown in Figs. 3(a) and 3(b), respectively. Reasonable accuracy is obtained except for a few




Figure 3: The absolute errors distribution in modelling the composition changes of Carbon dioxide, $\Delta\Gamma_{CO_2}$ over reaction time $12.5\mu s$: (a) neural network model, (b) repro-modelling function.

samples which constitute less than 10% of the sample space. The overall generalisation performance, measured in terms of the error function E_p ¹, of both methods are very good. However, it is better (smaller error function) for the ANN model ($E_p \approx 10^{-7}$) than that obtained by the RM technique ($E_p \approx 10^{-6}$). It is also observed that both methods suffer some degradation in accuracy if the modelled compositions are far enough outside the working range of the model. This result highlights the importance of selecting training samples that adequately represents the input/output combinations over a broad dynamic range. The appropriate selection of training set is currently an iterative trial and error procedure and

¹ $E_p \equiv \sum_{i=1}^N (d_i - y_i)^2$, represents the difference between the network's outputs, y , and the desired outputs d_i , over the N training samples.

the temperature (T) and mass fractions (Y) of H₂O and CO, obtained by MC simulation with ANN method compared favorably with experimental results. Whilst the current article is concerned with the application of ANN and RM to approximate chemical reactions in turbulent combustion simulations, the utilisation of these methods can be extended to applications for other non-linear system identification processes, such as the dynamics and control of a robotics arm

5. Conclusions

- Artificial neural network and Repro-Modelling approaches are successfully used to represent the chemistry of H₂/CO₂/O₂ mixture, accurately and efficiently.
- In general, both methods show good generalisation features, but the ANN approach exhibits better generalization capabilities than the RM functions. However, some degradation in the performance of both methods become noticeable once the modelled samples deviate significantly from the model's dynamic range.
- Both methods require a modest amount of computer memory. The computational cost of the RM approach is less than that of the ANN modelling, however the generalization of this observation is not conclusive, and require further investigation. The computation cost of both methods is much less in comparison to the CPU time of the direct integration approach. The storage requirement is also negligible compared with the storage demand of look-up tables.

Acknowledgments

The University of Sydney group acknowledges the support of the Australian Research Council. Dr. T. Turányi wishes to thank the support of IISF, OTKA grant No. F014481.

6. References

- [1] Peters, N., in: "Reduced Kinetic Mechanisms and Asymptotic Approximations for Methane-Air Flames", (Mitchell D. Smooke, Ed.), Springer-Verlag, Vol. 384, 1991, pp. 48-67.
- [2] Beale, R., and Jackson, T., *Neural Computing: An Introduction*, IOP Publishing, 1990.
- [3] Wu, Jian-Kang, *Neural Networks and Simulation Methods*, Marcel Dekker, Inc., 1994.
- [4] Turányi, T., "Application of Repro-Modeling for the Reduction of Combustion Mechanisms", *Twenty-Fifth Symposium (International) on Combustion*, The Combustion Institute, Pittsburgh, 1995, pp. 948-955.
- [5] Rogg, B., and Williams, F. A., "Structures of Wet CO Flames with Full and Reduced Kinetic Mechanisms", *Twenty-Second Symposium (International) on Combustion*, The Combustion Institute, Pittsburgh, 1988, pp. 1441-1451.
- [6] deVilliers, J., and Barnard, E., "Backpropagation Neural Nets with One and Two Hidden Layers", *IEEE Trans. on Neural Networks* Vol. 4., No. 1., Jan. 1992.
- [7] Christo, F. C., Masri, A. R., and Nebot, E. M., "Artificial Neural Network Implementation of Chemistry With PDF Simulation of H₂/CO₂ Flames", *Combust. Flame*, submitted (1995).
- [8] Turányi, T., "Parameterization of Reaction Mechanisms Using Orthonormal Polynomials", *Computers Chem.* Vol.18, No.1, pp. 45-54, 1994.
- [9] Nguyen, T. V., and Pope S. B., "Monte Carlo Calculation of Turbulent Diffusion Flames", *Combust. Sci. Tech.*, 42:13-45 (1984).